

Skid Mount Electric Vacuum Unit



## Standard Vacuum Unit Package features include the following:

- Power pack c/w 15 hp electric explosion proof w/ 480 V or 600 V 3ph
- · Low Oil shutdown safety sensor
- 2" x 5' recovery wand
- 8 " duckbill wand fitting c/w 2" camlock fitting
- 6 "straight wand attachment c/w 2" camlock fitting
- 12" moisture trap
- Options available:
- Electrical Class 1 Div 1
- · Integrated pump flush system
- · Integrated component drain system
- · Collection & Discharge hose package
- · Gasoline/Diesel powered
- 12" muffler & filter

- · Pressure relief safety valve
- · Vacuum breaker safety valve
- · Pressure/vacuum gauge
- · Full skid unit c/w forklift pockets
- · Owner/operator manual
- · One-year warranty



## Specifications and Serial Numbers

Unit SerialV			acuum Pump Serial
Electric Motor Type	Model _		Serial
Customer Name [		D	ate of Purchase
SVESK-400			
Pump			
Wallenstein			553 Oil Cooled Vane Pump
CFM			375
System Size			3"
Nominal Operating RPM			950
Discharge Pressure			10 - 12 PSI
Vacuum Continuous			20 (inches HG)
Vacuum Maximum			29 (inches HG)
Head Capability			15 - 20'
Hose Sizes			3" or 2" (Collection & Discharge)
Pulley Size			10.6" OD
Shaft Size			1 1/4" OD
Pump Oil			Hydraulic Oil (Non-Detergent)
Pump Oil Recommended			Summer 68 / Winter 32
Electric Motor			
Voltage			480 V or 600 V 3ph
Horsepower			15
Explosion Proof			Yes - Class 1, Div. 2
Amperage Draw			18
RPM			1760
Shaft Size			1 5/8" OD
Pulley Size			6" OD
Remote Start Station			Yes - w/100' cable
Tank			
Collection Tank Capacity			400 USG (1515 L)
Tank Size			42" x 68"
Tank Material			Steel
Access			16" Hatch
Weight & Dimensions			
Approx. Weight			2750 lbs. (1247 kg)
Dimensions			132" L x 44" W x 74" H
Paint			
Finish			Ероху
Colour			Innovex Green
Pump Flush	Standard YES	NO [	Integrated system YES NO
Muffler Drain	Standard YES	NO [	Integrated system YES NO